## (19) World Intellectual Property Organization

International Bureau



# 

(43) International Publication Date 13 January 2005 (13.01.2005)

**PCT** 

### (10) International Publication Number WO 2005/002372 A2

(51) International Patent Classification7:

A41C

(21) International Application Number:

PCT/US2004/020821

(22) International Filing Date: 24 June 2004 (24.06.2004)

(25) Filing Language:

English

(26) Publication Language:

**English** 

(30) Priority Data: 60/482,773


25 June 2003 (25.06.2003)

- (71) Applicant (for all designated States except US): S & S INDUSTRIES INC.; 32-00 Skillman Avenue, Long Island City, NY 11101 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HORTA, Joseph [US/US]; 15 Inwood Street, Yonkers, NY 10704 (US). THAKUR, Ajit; 2622 Lloyd Lane, Eagleville, PA 19403 (US). ROIZER, Sam [US/US]; 4 Yew Court, West Nyack, NY 10994 (US).

- (74) Agent: CATANZARO, Joseph, J.; Abelman, Frayne & Schwab, 150 East 42nd Street, New York, NY 10017-5612 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ADJUSTABLE UNDERWIRE ASSEMBLY



(57) Abstract: An adjustable underwire assembly for brassiere cups is disclosed, including a first generally U-shaped arcuate underwire member dimensioned and configured for insertion into a correspondingly generally U-shaped enclosure which extends along at least a portion of a first brassiere cup, and a second generally U-shaped arcuate underwire member dimensioned and configured for insertion into a correspondingly generally U-shaped enclosure which extends along at least a portion a second brassiere cup adjacent the first brassiere cup. A connecting and adjustment device connects the first generally arcuate member to the second generally arcuate member, the connecting device including a plurality of locking teeth or other locking surfaces or devices to selectively alter and maintain the relative angular orientation between the first and second generally arcuate members to facilitate adjustment of the brassiere cups as required by the wearer. The cups may be rotated downwardly for comfort, or upwardly for cleavage enhancement. Alternative configurations and optional locking devices are disclosed. A brassiere incorporating the adjustable underwire assembly is also disclosed.



## WO 2005/002372 A2



#### Published:

 without international search report and to be republished upon receipt of that report For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.